Kitek Technologier (Pot. Led.

KMS-701 WHEATSTONE BRIDGE TRAINER

SATIVE CENTRAL TO TUBE! STORY OF HUPPAY STORY OF THE TOTAL TO TUBE! STORY OF THE TOTAL TOTAL

- Wheatstone Bridge
- Potentiometer of 1K Ω
- 10KΩ potentiometer is a helical 10 turn pot mounted with dial for easy measurement
- Fixed Resistance10MΩ,1MΩ,100KΩ,10KΩ,1KΩ,100Ω & 10Ω available through Selector Switch
- One LED indicator to indicate Power input.
- OUTPUT Waveform Sine
- Variable Power DC supply: 0-15V
- All interconnections are made using 2mm banana Patch cords.
- Bare board Tested Glass Epoxy PCB is used.
- Test points are provided to analyze signals at various points.
- Set of 2mm Patch cords for interconnections

KMS-702 KELVIN BRIDGE TRAINER



- Kelvin Bridge
- Potentiometer of 1K Ω
- 10KΩ potentiometer is a helical 10 turn pot mounted with dial for easy measurement
- Fixed Resistance10MΩ,1MΩ,100KΩ,10KΩ,1KΩ,100Ω & 10Ω available through Selector Switch
- Block Description Screen printed on glassy epoxy PCB
- One LED indicator to indicate Power input.
- OUTPUT Waveform Sine
- All interconnections are made using 2mm banana Patch cords.
- Bare board Tested Glass Epoxy PCB is used.
- Test points are provided to analyze signals at various points.
- Set of 2mm Patch cords for interconnections

KMS-703 MAXWELL BRIDGE TRAINER



- Maxwell Bridge
- Potentiometer of 1K Ω
- 10KΩ potentiometer is a helical 10 turn pot mounted with dial for easy measurement
- Fixed Resistance10MΩ,1MΩ,100KΩ,10KΩ,1KΩ,100Ω & 10Ω available through Selector Switch
- Fixed Capacitance of 100µf,10µf,1µf,100kpf,10kpf,1kpf & 100pf available through Selector Switch
- Block Description Screen printed on glassy epoxy PCB
- One LED indicator to indicate Power input.
- OUTPUT Waveform Sine
- Fixed 1 KHz sine wave 3Vp-p is provided directly to M1 and GND is connected to M10
- All interconnections are made using 2mm banana Patch cords.
- Bare board Tested Glass Epoxy PCB is used.
- Test points are provided to analyze signals at various points.
- Set of 2mm Patch cords for interconnections

KMS-704 HAYS BRIDGE TRAINER



- Hays Bridge
- Potentiometer of 1K Ω
- 10KΩ potentiometer is a helical 10 turn pot mounted with dial for easy measurement
- Fixed Resistance10MΩ,1MΩ,100KΩ,10KΩ,1KΩ,100Ω & 10Ω available through Selector Switch
- Fixed Capacitance of 100µf,10µf,1µf,100kpf,10kpf,1kpf & 100pf available through Selector Switch
- Block Description Screen printed on glassy epoxy PCB
- One LED indicator to indicate Power input.
- OUTPUT Waveform Sine
- Fixed 10 KHz sine wave 3Vp-p is provided directly to H1 and GND is connected to H10
- All interconnections are made using 2mm banana Patch cords.
- Bare board Tested Glass Epoxy PCB is used.
- Test points are provided to analyze signals at various points.
- Set of 2mm Patch cords for interconnections